

**BOQ FOR KOTA FLOORING & WALL TILES WORK IN CLASS ROOM
AT DAV PUBLIC SCHOOL, HARRAKH BEGUSARAI**

SL.NO		DESCRIPTION	UNIT	QTY.	RATE	AMOUNT
1	15.23	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
	15.23.1	For thickness of tiles 10 mm to 25 mm	sqm	455.59		
2	15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	cum	35.77		
3	11.26	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete . Base with 1:1:1 (1 lime : 1 surkhi: 1 coarse sand) / 1:4 (1 cement: 4 coarse sand)				
	11.26.1	20 to 25 mm thick -	sqm	226.68		
4	11.27	Kota stone slabs 20 mm thick in risers of steps skirting. Dado & pillars laid on 12 mm (average (thick cement mortar 1:3 (1 cement: 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete. Details of cost for 10 sqm	sqm	39.02		
5	14.85	Taking out existing wooden door shutter,repair by cutting, paintingetc. and refixing of repaired door shutters to existing door frames,including replacement of hinges with screws, etc. as required, allcomplete as per the direction of the Engineer-in-charge.	NO	10.00		
6	13.93	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:				
	13.93.1	Two or more coats on new work	sqm	59.46		
7	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy , bottle green , black of any size as approved by Engineer-in-charge in skirting , risers of steps and dados over 12 mm thick bed of cement Motar 1:3(1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	sqm	208.47		
		Note:-				
	1)	Rate to be inclusive of GST				